

Spray Analysis

Size | Shape | Velocity

High performance size and velocity analysis tool

- Flexible mobile unit
- Operate in difficult applications
- Real time measurement
- Class I: laser eye safe
- Simple set-up, easy to use
- Industrial solution- stable, rigid, easy alignment









Image based - Gain vital insight into your process with real-time analysis



Built to handle ultra-fast moving sprays, the N60 is designed to capture clear images of small particles traveling at up to Mach 3; few things move too quickly for the VisiSize N60








Spray dried food product



Solid particles



Liquid in liquid droplets



Air inclusions in Agricultural spray





APPLICATIONS (partial listing)

- Agrochemical
- Fire suppression
- Vapour mitigation
- Automotive
- Food industry

A vast number of industries rely on sizing data from Oxford Lasers

STATISTICS REPORTED include: Mean diameter

(by number, area or volume), Sauter mean diameter, 10%, 50% and 90% volume percentiles,

Deviation, Relative Span.

SYSTEM SPECIFICATIONS

Application: Analysis of ultra-fast moving micron scale

droplets and particles

Velocity:

Size Range: >2µm, subject to application/configuration

Maximum particle velocity: 1,500m/s (50µm diameter particle)

Image source: Online, High resolution camera

up to 15,000 particles/second in

real-time mode.

Spray protection: Multi element cover - IP66 Cable length: 7m liquid light guide

10m camera cable

Typical working distance: >65mm, subject to application/configuration

Safety: Class I, laser safe

Contact us today for a free evaluation of your imaging and sizing needs:

OXFORD LASERS Ltd. Unit 8, Moorbrook Park, Didcot, Oxon, OX11 7HP, United Kingdom

OXFORD LASERS Inc. 2 Shaker Road, Unit A101 Shirley, MA 01464, USA

www.oxfordlasers.com | enquiries@oxfordlasers.com Tel: +1 (978) 425 0755